

# PVC SCHEDULE 40

## Specifications



### Injection Molded PVC SCH 40 Fittings:

- PVC Schedule 40 fittings are certified to meet or exceed all performance specifications of **ASTM D-2466**.
- PVC Schedule 40 fittings are manufactured using PVC compound cell class 12454, according to **ASTM D-1784**.
- PVC Schedule 40 fittings conform to the geometrics and patterns according to **ASTM F-1498**, the standard for tapered pipe thread for thermoplastic fittings.

### Reference

Complete line: 1/4" to 12"



### PVC SCH 40 Information:

TEMPERATURE RATING: 140°F. DERATE 50% AT 110°F AND 78% AT 140°F.

DO NOT USE FITTINGS FOR COMPRESSED AIR OR GASES.

SCHEDULE 40 PIPE SHOULD NEVER BE THREADED.

DO NOT USE FITTINGS WITH LIQUIDS NOT RECOMMENDED BY DURA/TIGRE.

MODIFICATION OF FITTINGS VOIDS THE WARRANTY.

SPECS SUBJECT TO CHANGE WITHOUT NOTICE.



#### Dura Plastics

customerservice@duraplastics.com  
1.951.845.3161  
www.duraplastics.com

#### Tigre USA

customerservice@tigre.com  
1. 608.754.4554  
www.tigreusa.com/